Lecture: Adopt a material

Advanced Technology Module Leader: Ilona Hav Technology Campion: Brian Murphy

Material Groups

- C01 C02 Ceramics
- F01 F02 Found Objects
- H01 H02 Hand Tools
- P01 P02 Plaster
- T01 T02 Timber
- TX01 TX02 Textiles

Your task: collate & record

- How it is made
- Raw materials, preparation, process, end product
- Strength, weakness, construction considerations
- Sourcing, production process, pollution caused carbon footprint, recycling
- Construction principles, typologies, details
- Compare with the other material groups

- Sketches, drawings, prototypes, tectonics, fabrication³

C01 C02 Ceramics

- · Starts as Clay from the ground
- Excavated subsoil (inert) below topsoil (alive)
- Blended: clays, straw reinforcement, fine sand aggregate, sawdust, mineral dyes
- Format: bricks, block, rammed earth, cob
- Wooden moulds, clay thrown into brick mould,
- Extruded and wire cut into bricks
- Can have texture added by roller
- Common bricks can have sand added to face
- Small balls into formwork and rammed in 75 mm layers squeezed to 50 mm visible layers

17/10/18 - Loadbearing

C01 C02 Ceramics

- · Can be sun/air dried: moisture driven off
- Solar energy intensive but free and no
- Sets dry but no curing nor strengthening
- Can be softened with water or steam
- Can reabsorb moisture vapour moderating humidity, avoiding need for ventilation or air conditioning

17/10/18

C01 C02 Ceramics

- Can be fired (cooked)
- High temperature, Energy intensive,
- Carbon level depends on fuel choice
- Clays can have an inherent fuel gas released by
- heat during firing but flue emissions increase
- Can be glazed (colour coated) for first firing
- · Can be double fired
- Terracotta: glazed for second firing
- Glazes: Matt to Gloss and big colour range

17/10/18

C01 C02 Ceramics

- Bricks, Glazed Bricks, Blocks,
- Floor/wall Tiles, Glazed tiles, Roof tiles
- Rain screen extrusions
- Ornate Sculpture (mimicking stone carving)
- Stone masons or clay modelers carved ornate pieces,
- Moulds made or taken, many copies made in terracotta
- Lightweight extruded hollow blocks
- insulating voids and long pathways make good U values · Crushed brick:

17/10/18 - consolidated hardcore, piling mat, brown roof gravel

C01 C02 Ceramics

- Increases with firing temperature
 And choice of clay
 Formation of structure: walls, timbrel arch,
- Engineering brick Damp Proof Course with strong cement mortar

- Thick walls: long delay Thin roof tiles: little protection
- Water or chemical-resistant (Grouting performance to match)
 Slip resistance: Glazed tile slip, unglazed grip

C01 C02 Ceramic

- · Rammed Earth Wall
- https://www.pinterest.co.uk/bmurphy1390/rammed-earth-
- https://www.pinterest.co.uk/bmurphy1390/cob/
- Brickwork
- https://www.pinterest.co.uk/bmurphy1390/f10-brickwork/ Mortar
- https://www.pinterest.co.uk/bmurphy1390/z21-mortar/ Roof wall tiles
- https://www.pinterest.co.uk/bmurphy1390/h6-slating-tilingroofing-cladding/
- Timbrel Arch
- 17/10/18 https://www.pinterest.co.uk/bmurphy1390/timbrel-arch-

F01 F02 Found Objects

Which materials: []
How it is made
Raw materials, preparation, process, end product
Inherent Properties
Strain Strain Strain Strain Strain Strain
Sustainability
Sourcing, production process, pollution caused, carbon footprint, recycling
Relevant Precedent Studies
Construction principles, typologies, details
Comparative Qualities
Compare with the other material groups

17/10/18 - Sketches, drawings, prototypes, tectonics, fabrication 10

F01 F02 Found Objects

- · Scope:
- Circular economy (dismantled building parts)
- Architectural Salvage (Hand crafted)
- Construction reclaim (others components)
- 'Dumpster diving' (with owners permission)
- (surplus to requirements, off-cuts, damaged)
- Materials Exchanges (surplus to requirements)
- Local Resource Locator websites
- Surplus to requirements. Returned to stock
- Industrial process waste: eg. lazar cut waste

710/18

F01 F02 Found Objects

- Environmental impacts:
 - Historic manufacture (so impacts ignored?)
 - LCA Life Cycle Analysis (impacts apportioned to main product and bi-product or co-product)
- Reclaimed Product Quality:
- Product Passport from first life/use
- Based on Product Specification
- See BAMB EU Horizon 2020 funded Project
- Buildings as Material Banks <u>www.bamb2020.eu</u>
 https://passports.bamb2020.eu
- User name: guest password: bambplatform

F01 F02 Found Objects

- Size is everything
 - Ideally modular and consistently so
- Designed to reduce waste in first use
- Design with the same in mind or waste more in second use
- Fixing methods is fundamental
 - Design for ease of assembly, dismantling and reassembly
 - State of repair in fixing zone
 - Take care of buried 'lost' fasteners

17/10/18

- They will wreck your tools: saws and drills
- · Companies with big magnets extract fasteners

F01 F02 Found Objects

- Lazar cutting scraps v efficiency iterations
- https://www.pinterest.co.uk/ bmurphy1390/resource-effectivedesign/

17/10/18

H01 H02 Hand Tools

- Which tools: [____] Which materials: [______]
- How it is made
- Raw materials, preparation, process, end product
- Strength, weakness, construction considerations
- Sourcing, production process, pollution caused, carbon footprint, recycling
- Relevant Precedent Studies
- Construction principles, typologies, details
- Compare with the other material groups
- 17/10/18 Sketches, drawings, prototypes, tectonics, fabrication

Hand Tools/ Hand crafted materials

- · Clay: See C01 C02 Ceramics above
- Plaster: See P01 P02 Plaster below
- Timber: See T01 T02 Timber below
- Textiles: See TX01 TX02 Textiles at end
- · Metals: See next
- Machining Materials: See after Metals

118

Metals

- Metals
 - https://www.pinterest.co.uk/bmurphy1390/ z11-metals/

Machining Sheet Materials

- Lazar cutting
- https://www.pinterest.co.uk/bmurphy1390/ lasar-cutting/
- CNC Milling
- https://www.pinterest.co.uk/bmurphy1390/ cnc-millingcutting/
- Resource Efficiency
 - Lazar cutting scraps v efficiency iterations
- https://www.pinterest.co.uk/bmurphy1390/ resource-effective-design/

P01 P02 Plaster

- Desulferisation gypsum (power station flue gas filtering)
- Diatomacious Earth (prehistoric ocean floor sediment)
- Bulking/Strengthening/texture/colour: Sand and fine aggregate - Reinforcement: horse hair, hemp shiv,
- insulating aggregates: Cork granules, hemp shiv,
- Cement/lime/sand,
- Lime/clay/diatomaceous earth/cork granules
- 17/10/18 Hemp/lime, Hemp/lime/cement/aluminium oxide

P01 P02 Plaster (internal) Render (external)

- · Properties:
 - Lime:

17/10/18

- . Alkali: Dangerous in the wrong hands (Not DIY)
- · Active waste: in landfill until hydrated, set and strengthened
- Anti bacteria

Performance & Application:

insulation function

- Hemp-lime:

predicted.

- Some add:

- · Moisture mass: moderates humidity
- Moisture permeable, moisture transport
- · Some carbon sequestration from atmosphere
- · Weaker than cement, flexible,
- · Reclaimable and recyclable (adding heat)
- · Medium density: medium thermal mass

P01 P02 Plaster

- Once fully hydrated (>1 year) performs far better than

. Cement for fast initial set and drive the lime to hydrate faster

Aluminium oxide to react with cement and foam up for

- Applied very thickly 300 mm not unusual

- Off site air drying can speed up process

- Exhibits a phase change characteristic

- Slow to set, hydrate, strengthen

P01 P02 Plaster

- Diatomacios earth/clay/lime/cork granules: Insulating:
 External Render, Internal Plaster, Floor Screed

· Properties:

- Cement:

- External Render, Internal Plaster, Floor Screed
 Airtight application, smooth or textured finish
 High thermal mass
 High decrement delay
 Summer solar protection
 Moisture Permeability (moisture escapes)
- - Hygroscopicity (Moisture buffering)
 Thicknesses: 40-100 normal
- much thicker possible
- Value engineering: One-coat one-trade multifunctional multi-performance finish

P01 P02 Plaster

- Solid walls:
 Masonry with raked joints for key
- Cast concrete with hessian in formwork Smooth concrete may need primer
 Wattle and daub
- oak strips weaved and lime plaster
 Metal meshes for gypsum plaster
- By hand: leaving hand and finger prints
- Mortar board > trowel > backing then trowelled smooth
- Projection: render flicked onto backing: good bond, peaky texture
 Pebble dash: texture and colour pebbles added to peaky surfaces
- Pumped through hose: smoothed by trowel
- Parge coats: airtight before plasterboard
- Plaster: airtight without plasterboard
 Wet trade requires time to dry before following trade (paint)

P01 P02 Plaster (internal)

Render (external)

· High embodied energy and carbon

· Water and water vapour resistant . Traps water in walls with no way out

· Inert waste in landfill once set

structural failure

buildings (pre 1919)

- (8-10% of manmade carbon dioxide)

· Stronger than lime, less flexible, less forgiving

- Saturates embedded timbers leading to rot and

Never use cement anywhere on or in historic

P01 P02 Plaster (internal)

17/10/18

· Properties:

- Clay: see C01 C02 Ceramics: (Unfired only)
 - · Internal only (unless protected from weat
- Moisture mass: moderates humidity
- · Absorbs smells, good for bathrooms
- Absorbs electromagnetic radiation (wifi etc)
- · High density: adds thermal mass
- Low skill and strength needed. DIY repairable
- · Add mineral dye; clay skim coats
- · Inert waste, add back to soil?

P01 P02 Plaster (internal)

Properties:

- Gypsum: (internal)
 - Lower embodied energy and carbon
- Water and water vapour resistant
- Traps water in walls with no way out
- Saturates embedded timbers leading to rot and structural failure
 Avoid gypsum plaster inside external walls in
- historic buildings (pre 1919) (use lime or clay)
- Stable Non-Reactive Hazardous waste in landfill (equivalent to asbestos for different reasons)
- Potential to react with landscape waste

Release sulfer to atmosphere making acid rain 17/10/18

- More expensive to dump so use it wisely

P01 P02 Plaster

Render

- https://www.pinterest.co.uk/bmurphy1390/ m21-external-insulation-with-renderedfinish/
- Cob
 - https://www.pinterest.co.uk/bmurphy1390/

© GBE NGS ASWS 2018 Brian Murphy

T01 T02 Timber

- · Raw materials: (A seasonal crop)
 - Hardwood: Deciduous, Broadleaf
 - Softwood: Coniferous, Pine needs and cones
 - Moonwood: winter: low sap, night time, least moon gravity, (sacred in some societies?)
- · Manufactured:
 - Glulam Glued laminated wood: frames · (strength where its needed, weaker where it is not)
 - LVL Laminated Veneer Lumber
 - · (using thinnings, thin layers same direction)
 - CLTP Cross Laminated Timber Panels
- (using thinnings, softwood/plywood in layers)

- Other compound sections

T01 T02 Timber

· Timber Panel Products:

- layers at right angles - Particleboard:
- · Chipboard (chips), · OSB (shavings),
- Wood fibre boards.
- MDF Medium density fibreboard
- · medium board.
- Wood fibre Insulation boards and batts
 - . Breathing, sheathing, thermal + acoustic insulating,

T01 T02 Timber

- Ingredients:
 - Treatment: (killing chemistry)
 - · Preservatives, Fire protection,
 - · rot resistant, insect resistant
 - Salts: added to recipe
 - · offering any of above treatments
 - · Borax mineral (as benign as possible)
 - Heat Treatment: Remove nutritional

content for Durability

T01 T02 Timber

- Assembly:
 - Geometry, mechanical connection, friction, aravity
 - Adhesives:
 - · Historic: animal glue;
 - · Modern: synthetic high performance
 - Fasteners:
 - · Historic: Hardwood Dowels,

17/10/18

· Modern: Metals, plastic, chipboard biscuit,

T01 T02 Timber

- Photosynthesis: nature converting sunlight and Carbon dioxide into
- cellulose and oxygen (great synergy with humans)

 Carbon Dioxide Sequestration = Carbon negative
- Low energy input with carbon based petrol chain saws - Transport emissions or floated down rivers, if not remote
- Forests: but ideally very selectively leaving forest intact
 Plantations: thinnings or the final crop
- Replanting more trees not palm oil: Sustainable management
- looking after nature and indigenous people
- FCS Forest Stewardship Council 'or equivalent
- Certified legal: Just got easy
 EUTR EU Timber Regulations EU Funded Project

 - www.nepcon.org/sourcinghub

T01 T02 Timber

- Processing:
 - Debarked (cork comes from bark)
- Sapwood removed (Perishable recently living, with sap flowing in the veins)
- Heartwood saved (durability resides here)
- Sawing, cutting arrangement (waste in sawdust and scraps)
- Planing, leaving rough or adding texture
- Waste scraps: fuel or into timber panel products
- Machining Energy's carbon: reduces the carbon negativity of timber (but not a lot)

T01 T02 Timber

- Properties
 - Durability:
 - · depends upon species
 - · will change if grown in different climates
 - · is classified and applicable to end use
 - Grain:
 - · give strength in one direction and weakness in others
 - figuring is not always the same as grain
- Machine able to varying degrees:
- · grain direction dictates, craftsmen know-how
- Designers/Engineers exploit grain direction
- 17/10/18 Manufacturer invent products to solve weaknesses

T01 T02 Timber

- https://uk.video.search.yahoo.com/yhs/search?fr=yhs-imt-
- · Drawbored M&T joint with very different approach in 10
 - https://uk.video.search.yahoo.com/yhs/search?fr=yhs-imt-
- +video#id=6&vid=76f979695f3693e3545e83b045019817&action=view And some serious 3D dovetails and a whole lot more in 16
- minutes

- Paul Sellers does a fine job of a Mortice and Tenon joint in 30 minutes, very detailed commentary
 - brwsrex&hsimp=yhs-brwsrex&hspart=imt&p=mortice+and+tenon+joint +video#id=1&vid=6373eb34d00240e8cc58fdd3b7a112dc&action=click
- minutes, with the magic touch at the end
- brwsrex&hsimp=vhs-brwsrex&hspart=imt&p=mortice+and+tenon+ioint
- https://www.youtube.com/watch?v=0kgCsZJGluc

T01 T02 Timber

- · Connecting: Fixings Fastenings
- https://www.pinterest.co.uk/bmurphy1390/z20-connectivity/
- · Timber Structure
- https://www.pinterest.co.uk/bmurphy1390/g20-timber/
- - https://www.pinterest.co.uk/bmurphy1390/z10-purpose-
- · Shingles and Shakes
- https://www.pinterest.co.uk/bmurphy1390/h64-shingles-shakes/
- Plywood furniture
- https://www.pinterest.co.uk/bmurphy1390/n20-plywood-furniture/

TX01 TX02 Textiles

- Carpet/rugs, underlays,
- Hung fabrics
- Stretched fabrics,
- Furniture upholstery.
- Gentextiles
- Recycled fabric insulation (denim, cotton)
- animal wool/hair: sheep's wool.
- insect: cotton, spiders web, silk,
- Animal or fish leather
- Synthetic plastics, Bio-plastics
- Blends of natural and technical/synthetic
 - . (contrary to Cradle to Cradle C2C principles)

TX01 TX 02 Textiles

- · Applications & Performance:
- · Carpet: Thermal insulation: Thermal Comfort. Acoustic: Absorption, Tactile
- · Curtains: Solar control, Privacy, Black out, Draft lobby at doors, Thermal insulation at windows, Fire resistance (Stage curtain)
- · Wall and Ceiling linings: Decoration, Colour, Acoustic Absorption, may need to be low surface spread of flame and non-combustible
- · Furniture: Linings, Upholstery (fire/smoke propeties)

TX01 TX02 Textiles

- persist), animal droppings, tangles, thorns, seeds/husks, insect eggs,
- Process: separating, washing, carding, combing, dying, weaving, trimming, edging, sewing
- · Impacts: unhealthy dip, waste, chemically intensive dying, water polluting, waterway/ waterbody polluting.
- Additional treatments: moth deterrent, fire 17/10/18 treatment in upholstery 38

Feedback

- These files are created by generalists with a big dollop of green flavour
- These files are updated from time to
- We are not experts so from time to time these file may get out of date or may be
- · If you feel that we have got it wrong 17/10/18 please let us know so we can put it right

TX01 TX02 Textiles

- · Weaving gives strength, texture, pattern, rhythm, colours
- · Different weaves make fabric hang/flow/ stretch/shrink/hug differently
- · Treatments improve: fire properties, durability
- · Some moth killer treatments:
- CNS Central Nervous System depressants
- Invented by Germans to kill British in WW World
- 17/10/18 Now we douse our carpets and fabrics

© GBE 2018

- annehed www.arhttps://greenbuildingencyclopaedia.uk 2015
 BrianSpecMan@icloud.com
 witter: http://witter.com/brianspecman
 witter: GBEGreenBuild @GBEGreenBuild
- BrianSpecMan
- BrianSpecMan Facebook: http://www.facebook.com/brianspecma Google+: BrianSpecMan • BrianSpecMan CAPEM • NGS National Green Specification
- Slide Share:
 Pinterest: Brian Murphy GBE Green Building Encyclopaedia
- CAP'EM: GreenSpec & NGS

- CAP EM Compass

 17/10/18 LSBU London South Bank University Faculty and Course website page Brian Murph